

Integration paving

Integration paving was created for people who are blind and visually impaired. There are **characteristic nozzles on its surface** that serve as a **warning** against changing direction and the height of the ground, an obstacle or approaching a hazardous area. Such a ground is readily **discernible both tactilely** (e.g., with feet or stick) and **acoustically**, which directly increases the safety of people with low vision. Integration paving in **public space should be used** wherever there is any threat to the blind and visually impaired, e.g. **along the edges of sidewalks, platforms, before entering the crosswalk** or at the beginning and end of each **flight of stairs**.



Color chart

Standard



red



Attention: Colours with a phone icon: Only on order product.

Recommendations and information:

Installation in accordance with the construction practice. Use with a traffic load of more than 3.5 t and heavy traffic KR3 is subject to the roadbase being constructed in accordance with the manufacturer's guidelines contained in the product documentation.

All surfaces should be constructed in accordance with the guidelines of the Minister of Transportation (Catalog WR-D-63). Product should be laid only on a sand or sand cement bedding.


Bevel: classic dimension bevel

Spacers: classic dimension (suitable for combination with Brick paving)

Joint width: 3-5 mm

Production: made with the use of the two-ply technology

Shapes and dimensions



Product details

- Number of elements in the system:** 1
- Appearance:** flat surface and straight edges, the face with dome nozzles
- Thickness (cm):** 8
- Format:** medium
- Designation:** driveways and car parks, walkways, terraces, garden/paths/alleys, roads
- Loads:** vehicle traffic: load up to 3,5 t, vehicle traffic: load over 3,5 t, low heavy traffic (KR3)., pedestrian traffic
- Material:** vibro-pressed concrete

Logistic data

| Pallet weight [kg] | Number of m2 per pallet |
|-----------------------------|-------------------------|
| 1480 | 8,64 |
| | |
| Number of layers per pallet | |
| 8 | |

Attention: For technological reasons pallet's weight may change.

See the product online on your smartphone

