

Nowa 28 G Street 44-352 Czyżowice phone: 32 456 09 70 / 32 456 09 71 biuro@bruk.info.pl www.bruk.info.pl www.modernline.info.pl

STRUCTUR Double-slop cap

The double-slope cap is an element crowning the fence. It may be used for finishing fence walls, bases or posts. The cap serves as a decoration and protection: it secures structures made of split face hollow blocks against the adverse atmospheric conditions. Its surface enables the drainage of water.

The cap is available in **two sizes and colours** matching the fence wall and post elements of the collection of split fence systems by Bruk.



Color chart

Splitted





Attention: Colours with a phone icon: Only on order product.

Recommendations and information:

Installation on **frost-proof glue**. Sealing **with silicone** necessary. Installation after a **minimum of 2 days** from the time of filling the walls and pillars with concrete. It is recommended to **impregnate** with an agent preventing the accumulation of dirt and moss fouling after a minimum of 30 days from the end of assembly works.


Recommended for use with Structur fencing blocks.


Drips: none

Production: made with the use of the one-ply technology and splited

Attention: For technological reasons pallet's weight may change.

Shapes and dimensions





Product details

Number of elements in the system: 1

Appearance: flat surface and straight edges, 2 sizes

Designation: finishing and protection of the fence walls and posts

Material: vibro-pressed concrete

Logistic data

Pallet weight [kg]

30x24x6 cm: **175**

48x24x7 cm: **345**

Number of pieces per pallet

30x24x6 cm, 48x24x7 cm: **24**

Number of layers per pallet

1

See the product online on your smartphone

